



Temporary Power Solutions
Power when you need it
 0800 772 3193

Ecolite-T



Environmentally focused lighting tower

Ecolite T lighting tower uses modern, energy efficient Ceramic Discharge Metal Halide technology which combined with our patented prismati lenses produces superior definition, clarity and colour at a fraction of the CO₂ output associated with any other lighting tower.

Features

- Long run time – up to 170 hours on one tank
- Safe working environment – reduced glare from ceramic discharge lamps and patented lens technology
- Quiet running – ideal for use at outdoor events
- Robust 9.1m hydraulic mast – able to withstand winds of up to 100kmph (62mph/ Beaufort Scale 10)
- Bunded base – 110% machine fluids containment
- Dusk to dawn auto switching
- Auxiliary power output 220V or 110V.

Benefits

Zone 2 compliant model available with:

- Spark arrestor
- Chalwyn valve
- Braided fuel lines
- Fuel shutdown valves
- Battery isolator
- Desert Pack model available
- Additional safety system AMOSS (Automatic Mast Operating Safety System).



Specification

PERFORMANCE

Maximum Power Output	3.1kW	Noise Level	85d Ba LWA
Operating Voltage	12V DC/220V AC	Braking System	Park and Over-run
Lamps	4 x 250W	Maximum Wind Speed	100kmph (62mph)

ENGINE

Make	Hatz 1B20	Engine Oil Capacity	2.6 Litres
Fuel	Diesel	Fuel Consumption With Lights Only	0.5 Litres/Hour
Fuel Tank Capacity	95 Litres	Total Run Time On Full Tank	170 Hours

DIMENSIONS AND WEIGHT

Length	2500mm	Width	1345mm	Height Lowered	2150mm	Height Fully Extended	9100mm
Tow Hitch Height	440mm	Overall Width With Stabilisers Fully Extended	2105mm	Wheel Size	165 R13	Ground Clearance	244mm

Call us: 0800 772 3193

sales@temporarypowersolutions.co.uk www.temporarypowersolutions.co.uk
 Plot 6, The Falcon Estate, North Feltham Trading Estate, Feltham, Middlesex TW14 0XJ